



## EUROVAC-A

### Main Applications



- Hospital Crash Carts
- Patient Transfer
- Long Term Home Care
- Tracheostomy
- EMS / Ambulance
- Bed Side

## MULTIVAC

### Main Applications

- Hospital Crash Carts
- Patient Transfer
- Long Term Home Care
- Tracheostomy
- EMS / Ambulance
- Bed Side

## TECHNICAL FEATURES

Model	EUROVAC - A BATTERY OPERATED SUCTION UNIT	MULTIVAC BATTERY & MANUAL OPERATED SUCTION UNIT
Housing	MS Powder Coated	MS Powder Coated
Max. Vacuum / LPM	600 mm Hg, 21 Ltrs / min	Electrical : 600 mm Hg, 21 Ltrs / min Pedal : 200 ml / push stroke
Pump Type	Piston pump	Piston pump
Jars	1 x 0.5 Ltr. PC Jar	1 x 1 Ltr. PC Jar
Filter	Bacterial Filter Autoclavable / Reusable	Bacterial Filter Autoclavable / Reusable
Tubing	8 mm ID x 2 mtr. (Silicon)	8 mm ID x 2 mtr. (Silicon)
Vacuum Gauge	5 cm dia 0-760 mm Hg	Bourdon type 5 cm dia 0-760 mm Hg
Power Supply	220 V AC, 50 / 60 Hz, 70 Watt, 12 V DC Internal Rechargeable Battery (12 V 4.5 Amp)	220 V AC, 50 / 60 Hz, 70 Watt, Electric - Pedal 12 V DC Internal Rechargeable Battery (12 V 4.5 Amp)
Noise Level	55 dB A ± 3	55 dB A ± 3
Battery	Lead Acid	Lead Acid
Battery Backup / Operative Time	90 minutes (with fully charged /new battery)	90 minutes (with fully charged /new battery)
Dimensions	37 x 14 x 30 cms	33 x 30 x 41 cms
Net Weight	5.5 Kg	8.5 Kg
Overflow Safety	Mechanical & Electronic Sensor 	Mechanical & Electronic Sensor 
Accessories	Car Charger & Power Adaptor	Car Charger & Power Adaptor
Optional	Ni-cd / Li-ion Battery	Ni-cd / Li-ion Battery
Certifications	CE, IEC 60601-1-2012	CE, IEC 60601-1-2012