



Back View

EUROVAC ADVANCE

Main Applications

- Intensive Care Unit
- Room / Ward
- Dental Practice
- Home Care
- Eye / ENT

TECHNICAL FEATURES

Model	EUROVAC ADVANCE	
Housing	ABS Plastic Moulded with two castors & changeover lever	ABS Plastic Moulded
Max. Vacuum / LPM	600 mm Hg, 45 Ltrs / min	600 mm Hg, 30 Ltrs / min
Pump Type	Oil-free Double Diaphragm Pump	Diaphragm Pump
Jars	2 x 2 Ltr. PC Jar, Autoclavable	1 x 2 Ltr. PC Jar
Filter	Bacterial Filter Autoclavable / Reusable	Bacterial Filter Autoclavable / Reusable
Tubing	8 mm ID x 2 mtr. (Silicon)	8 mm ID x 2 mtr. (Silicon)
Vacuum Gauge	6.25 cm dia 0-760 mm Hg	6.25 cm dia 0-760 mm Hg
Power Supply	220 V AC, 50 / 60 Hz, 90 Watt	220 V AC, 50 / 60 Hz, 90 Watt
Noise Level	55 dB A ± 3	55 dB A ± 3
Dimensions	43 x 22 x 37 cms	43 x 22 x 37 cms
Net Weight	10 Kg	8 Kg
Overflow Safety	Mechanical & Electronic Sensor	Mechanical & Electronic Sensor
Optional	110 V	110 V
Certifications	CE, IEC 60601-1-2012	CE, IEC 60601-1-2012

